

MITSUBISHI OD-10



Technical information

LEDer Module	Mitsubishi AVL OD-10
Display device	Light Emitting Diode (LED)
Pixel Pitch	10mm
Display area	1.23 m2
Resolution	10,000 dots/m2
Brightness	5000 Nits
1 Module	1.28m x 0.96m x 0.256m (wxhxd)
Weight	95 kg
Minimum viewing distance	6 m
Viewing angle horizontal	+/- 80 degrees
Viewing angle vertical	+/- 15 to 30 degrees
Power peak consumption	1.5 KVA
Power supply	380-415V 3 phases + neutral = earth

Creator of live experiences

4:3 Screens

Screen	Width (M)	Height (M)	Area (m2)	Weight (kg)
3x3	3.84	2.88	11	900
4x4	5.12	3.84	20	1600
5x5	6.40	4.80	30	2400
6x6	7.68	5.76	44	3500
7x7	8.96	6.72	60	4900
8x8	10.24	7.68	79	6400
9x9	11.52	8.64	100	8100



16:9 Screens

Screen	Width (M)	Height (M)	Area (m2)	Weight (kg)
4x3	5.12	2.88	15	1200
5x4	6.40	3.84	25	2000
6x5	7.68	4.80	37	3000
7x5	8.96	4.80	43	3500
7x6	8.96	5.76	52	4200
8x6	10.24	5.76	59	4800
8x7	10.24	6.72	69	5600
9x7	11.52	6.72	77	6300
10x8	12.80	7.68	98	8000

