

MITSUBISHI ODQ-8 MODULAR LED SYSTEM.

FABER
AUDIOVISUALS

SPECIFICATIONS

Outline drawing of standard rental module

<i>MODEL NUMBER</i>	<i>ODQ-8</i>
<i>DESCRIPTION</i>	<i>LED RENTAL MODULE</i>
<i>APPLICATION</i>	<i>OUTDOOR USE, RENTAL MARKET</i>
<i>PIXEL ARRANGEMENT</i>	<i>DYNAMIC PIXEL, LAMP TYPE, 2R 1G 1B, PURE COLOUR</i>
<i>PIXEL PITCH</i>	<i>16.00MM</i>
<i>DOT PITCH</i>	<i>8.00MM</i>
<i>PIXEL RESOLUTION PER RENTAL MODULE</i>	<i>96H x 128W = 12,288 DOTS</i>
<i>PIXEL DENSITY PER SQ/M</i>	<i>15,625 DOTS PER SQUARE METRE</i>
<i>MINIMUM VIEWING DISTANCE</i>	<i>MINIMUM 6 METRES</i>
<i>BRIGHTNESS</i>	<i>5000 CD/M2</i>
<i>LIFETIME TO 50% BRIGHTNESS</i>	<i>50,000 HR</i>
<i>IMAGE PROCESSING</i>	<i>PROGRESSIVE SCAN CONVERTER AND INTERPOLATION</i>
<i>PROCESSING (GREYSCALE)</i>	<i>12-BITS, EQUIVALENT TO 4,096 STEPS</i>
<i>PROCESSING (COLOUR)</i>	<i>18-BITS</i>
<i>REFRESH RATE (PAL/NTSC)</i>	<i>800/960Hz</i>
<i>VIEWING ANGLE</i>	<i>VERTICAL +/- 30°, HORIZONTAL +/- 70°</i>
<i>TEMPERATURE RANGE</i>	<i>0 - 40 °C (32 - 104 °F)</i>
<i>MODULE DIMENSIONS</i>	<i>HEIGHT: 768MM, WIDTH: 1024MM, DEPTH: 230MM</i>
<i>SERVICE ACCESS</i>	<i>FRONT AND REAR</i>
<i>MODULE WEIGHT</i>	<i>80KG</i>
<i>POWER CONSUMPTION</i>	<i>0.6KW/SQ.M. BASED ON 100% BRIGHTNESS AT 30% DUTY.</i>
<i>INPUT POWER CABLE</i>	<i>AC200V TO 240V 3PHASES 3WIRES 50/60Hz</i>

Creator of live experiences

