

ODECO 16MM SMD



Specification

Technology

| | |
|-------------------------|--------------------------------------|
| LED | SMD (3 in ONE) |
| Board Configuration | 16 x 8 pixels |
| Pixel Configuration | 1 RED, 1 Green, 1 Blue in single SMD |
| LED's m2 | 3,669 pixels m |
| Distance between pixels | 16.51 horizontal / 16.51 Vertical |
| Angle of Vision h/v | 120 / 120 |
| Pixel | MultiLedRGB |
| Luminosity at 6.500 | 5,500 nits |
| Dimming | 256 steps per colour - 16 levels |
| Colours | 1.074 millions |

Modular Characteristics

| | |
|------------------------|--|
| DIMENSIONS | 2.642 X 975 X 175 mm |
| Active Area | 2.643x 924 mm |
| Pixel pitch | 160 x 56 pixels (w x h) |
| Total pixels | 8.960 pixels |
| Frontal Protection | Polycarbonate bubble ready for impacts |
| Temperature: Operating | -10 till 60 C |
| Temperature: Storage | -20 till 85 |
| Weight approx. | 100 kg |

Inputs / Power

| | |
|-------------------------------|---------------------------------|
| Singnal Input | input to X/VGA |
| LED Life: | 70.000 hours |
| Files & animations | BMP / MPEG1 / AVI / JPEG / TEXT |
| Software | Customized |
| Power supply | 24 vcc / 220-380 V / 50 Hz |
| Average power | 630 W / linear meter |
| Maximum Power (white 100%dim) | 1050 W / linear meter |



Creator of live experiences